



## PRODUCT SPECIFICATIONS 2008

Registered Brand:	B-Fix®
Model:	B-Fix Border
Manufacturer:	Sindrila sprl
Origin:	Bierges – Belgium
Recommended materials:	Exotic hardwoods with a minimum depth of 20mm and a maximum width Of 160 mm. Ideal deck board: 20/140 mm profiled with a B-Fix model Leitz routing bit (Hardwood floor joists placed every 49cm).
Tested Wood Species:	Ipe, Padouk, Afrormosia, Cumaru, Itauba, Garapa, Tali, Limbali, Larch, Douglas-Fir, Bamboo
Installation:	B-Fix allows up to a 40% saving in terms of installation time compared with traditional (plug) methods.
Dimensions:	B-Fix Border: 40mm x 58mm x 8,5mm, Border-Screw: 5mm x 40mm – Tx 20
Composition:	B-Fix Border: stainless steel 301, Border-Screw: stainless steel A2
Finish:	Bronze tinted stainless steel
Advantages:	Unalterable, aesthetic, easily dismantled (from the front), simple to use.
Edge:	The B-Fix Border system allows the outside edge of the first deck board to be flush with the edge of the supporting structure, whilst hiding the screws. The inside edge of the first deck board is then fastened with B-Fix One.
Expansion/Contraction:	B-Fix Border (and B-Fix One) has a spring memory effect designed to allow the deck board to expand and contract naturally while bringing it back systematically to its initial position.
Recommended Screw:	B-Screw
Moisture Content:	The recommended moisture content is 18%, regional moisture content = (mc summer + mc winter)/2. Ex: Le Zoute, (24+18)/2 = 21, Brussels, (22+16)/2 = 19, Lille, (22+14)/2= 18; Marseille (17+11)/2= 14
Consumption Ratio:	20/140mm deck boards: depends on the spacing between the flooring joists. Recommended spacing: every 40 to 50cm.
Package Content:	5 sachets of 10 B-Fix Border fasteners & 10 B-Screws, 1) assembly instructions
Package Dimensions:	180mm x 95mm x 55mm
Package Weight:	1,1 kg.
Label:	Logo, contents, code bar: 54250188600029, weight, manufacturers' address.
Code Bar - Sachets:	5425018860036
Other Questions:	



[www.ecobati.be](http://www.ecobati.be)  
[info@ecobati.be](mailto:info@ecobati.be)  
 tel : +32 (4) 246 32 49  
 fax : +32 (4) 247 06 07