



## PRODUCT SPECIFICATIONS 2008

Registered Brand	B-Fix®
Model	B-Fix One
European Patent	03100449.2
Manufacturer	Sindrila sprl
Origin	Bierges – Belgium
Recommended Materials	Exotic hardwoods with a minimum depth of 20mm and a maximum width of 160 mm. Ideal deck board: 20/140 mm profiled with a Leitz, B-Fix model routing bit, (Hardwood floor joists placed every 40-50cm)
Tested Wood Species	Ipe, Padouk, Afrormosia, Cumaru, Itauba, Garapa, Tali, Limbali, Larch, Douglas-Fir, Bamboo
Installation	B-Fix allows up to a 40% saving in terms of installation time compared with traditional (plug) methods.
Dimensions	B-Fix: 40mm x 34mm x 8,5mm B-Screw: 5mm x 35mm – Tx 20
Composition	B-Fix: stainless steel 301 B-Screw: stainless steel A2
Finish	Bronze tinted stainless steel
Advantages	Unalterable, aesthetic, easily dismantled (from the front), simple to use.
Spacing	B-Fix will automatically create a 4,5 to 5mm gap between each profiled decking board
Expansion/Contraction	B-Fix has a spring memory effect designed to allow decking to expand and contract naturally while bringing it back systematically to its initial position. The first decking board should be placed 4mm from the wall.
Recommended Screw	B-Screw
Moisture Content	The recommended moisture content is 18%, regional moisture content = (mc summer + mc winter)/2. Ex: Le Zoute, (22+18)/2 = 20, Brussels, (22+16)/2 = 19, Lille, (22+14)/2= 18; Marseille (17+11)/2= 14
Consumption Ratio	20/140mm decking boards: 17 B-Fix/m², 20/100mm decking boards: 23 B-Fix/m²
Package Content	(100) B-Fix, (100) B-Screws, (1) 20 x 50mm Torx bit, ( 1 ) assembly insrtructions
Package Dimensions	210mm x 155mm x 80mm
Package Weight	1,9 kg.
Label	Logo, contents, bar code: 5425018860012, weight, manufactuers' address
Other Questions	



[www.ecobati.be](http://www.ecobati.be)  
[info@ecobati.be](mailto:info@ecobati.be)  
 tel : +32 (4) 246 32 49  
 fax : +32 (4) 247 06 07